

TS-800

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-800	2.75-18	1.85×18	4PR	75/2.95	613/24.1	150/330	TT
		1.85×18	6PR	75/2.95	613/24.1	180/395	TT
		1.85×18	8PR	75/2.95	613/24.1	195/430	TT
	2.75-17	1.85×17	4PR	75/2.95	588/23.1	145/320	TT
		1.85×17	6PR	75/2.95	588/23.1	175/385	TT
		1.85×17	8PR	75/2.95	588/23.1	190/420	TT
	3.00-18	1.85×18	4PR	80/3.15	627/24.7	175/385	TT
		1.85×18	6PR	80/3.15	627/24.7	200/440	TT
		1.85×18	8PR	80/3.15	627/24.7	218/480	TT
	2.50-17	1.60×17	4PR	65/2.56	568/22.4	132/290	TT
		1.60×17	6PR	65/2.56	568/22.4	155/340	TT
		1.60×17	8PR	65/2.56	568/22.4	165/365	TT
	110/90-16	2.50×16	59P	109/4.29	604/35.6	243/535	TT/TL
		2.50×16	65P	109/4.29	604/35.6	290/640	TT/TL

TS-801

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-801	4.10-18	2.15×18	4PR	104/4.09	639/25.2	243/535	TT
		2.15×18	6PR	104/4.09	639/25.2	272/600	TT

TS-802

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-800	3.00-18	1.85×18	4PR	80/3.15	627/24.7	175/290	TT/TL
		1.85×18	6PR	80/3.15	627/24.7	200/440	TT/TL
		1.85×18	8PR	80/3.15	627/24.7	218/480	TT/TL
	2.50-17	1.60×17	4PR	65/2.56	568/22.4	132/290	TT
		1.60×17	6PR	65/2.56	568/22.4	155/340	TT
		1.60×17	8PR	65/2.56	568/22.4	165/365	TT
	2.75-17	1.85×17	4PR	75/2.95	588/23.1	145/320	TT
		1.85×17	6PR	75/2.95	588/23.1	175/385	TT

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
		1.85×17	8PR	75/2.95	588/23.1	190.42	TT